

# Declaration of performance

ESD/DOP-No 001/CPR/2016.01.01

1. Product type identification code	BT 70 AD
2. Identification No	BT 70 AD-D/DK-1,1-0,62-0,04-34
3. Application	Opening/tilting windows, doors and glass walls for residential and non-residential construction
4. Manufacturer	UAB "Aradas", registration number 301818042 Gamybos str. 12, LT-62175, Alytus
5. Authorised representative	-
6. Performance assessment system	3
7. Conformity standard:	<b><u>DS/EN 14351-1:2006+A2:2016</u></b> + A1:2010
8. Notified testing authority:	ift Rosenheim NB-Nr. 0757, as the notified test laboratory, performed the initial tests of system 3 and provided the control and classification reports.

---

## 9. Basic characteristics:

Declared properties	Results	Harmonised technical specifications
Rain/water tightness	E900	<b><u>DS/EN 14351-1:2006+A2:2016</u></b> : 4.5
Dangerous substances	-	<b><u>DS/EN 14351-1:2006+A2:2016</u></b> : 4.6
Wind resistance	B5	<b><u>DS/EN 14351-1:2006+A2:2016</u></b> : 4.2
Bearing capacity of safety devices [N]	350	<b><u>DS/EN 14351-1:2006+A2:2016</u></b> : 4.8
Sound insulation [dB]	34 (-2;-5)	<b><u>DS/EN 14351-1:2006+A2:2016</u></b> : 4.11
Thermal conductivity coefficient [W/m <sup>2</sup> K]	1,3	<b><u>DS/EN 14351-1:2006+A2:2016</u></b> : 4.12

## Radiative properties:

General energy permeability	62%	
Light transmission degree	82%	<b><u>DS/EN 14351-1:2006+A2:2016</u></b> : 4.13
Air penetration	4	<b><u>DS/EN 14351-1:2006+A2:2016</u></b> : 4.14

---

10. The product properties under paragraphs 1 and 2 conform to the properties declaration No 9.

On behalf of the manufacturer:

L. S.

signature:

# Declaration of performance

ESD/DOP-No 002/CPR/2014.01.01

1. Product type identification code	BT 70 AD
2. Identification No	BT 70 AD-D/DK-0,6-0,54-0,04-34
3. Application	Opening/tilting windows, doors and glass walls for residential and non-residential construction
4. Manufacturer	UAB "Aradas", registration number 301818042 Gamybos str. 12, LT-62175, Alytus
5. Authorised representative	-
6. Performance assessment system	3
7. Conformity standard:	EN 14351-1:2006 + A1:2010
8. Notified testing authority:	ift Rosenheim NB-Nr. 0757, as the notified test laboratory, performed the initial tests of system 3 and provided the control and classification reports.

---

## 9. Basic characteristics:

Declared properties	Results	Harmonised technical specifications
Rain/water tightness	E900	EN 14351-1:2006 + A1:2010: 4.5
Dangerous substances	-	EN 14351-1:2006 + A1:2010: 4.6
Wind resistance	B5	EN 14351-1:2006 + A1:2010: 4.2
Bearing capacity of safety devices [N]	350	EN 14351-1:2006 + A1:2010: 4.8
Sound insulation [dB]	34 (-2;-6)	EN 14351-1:2006 + A1:2010: 4.11
Thermal conductivity coefficient [W/m <sup>2</sup> K]	0,9	EN 14351-1:2006 + A1:2010: 4.12

---

## Radiative properties:

General energy permeability	54%	
Light transmission degree	74%	EN 14351-1:2006 + A1:2010: 4.13
Air penetration	4	EN 14351-1:2006 + A1:2010: 4.14

---

10. The product properties under paragraphs 1 and 2 conform to the properties declaration No 9.

On behalf of the manufacturer:

L. S.

signature: